



Product Overview

LB1930MC: Motor Driver, Bidirectional, Low Voltage, Low Saturation

For complete documentation, see the data sheet

Product Description

The LB1930MC is single-channel forward/reverse DC brush motor driver. This device is optimal for CD, DVD and Blue Ray Disk player loading motors. And it is possible to use it for others as a general-purpose product.

Features

- The LB1930MC features the wide operating voltage range of 2.2 to 10.8V and the low standby current drain of 0.1A, and therefore can easily be used in battery operated systems.
- To minimize through currents, the LB1930MC internal logic passes through an internal standby state when switched by the input signals between forward/reverse and brake, or between forward and reverse.
- If the IC chip exceeds 180C due to an output short causing a large current flow, the built-in thermal protection circuit suppresses the drive current to prevent fires or destruction of the IC.
- Zero power consumption in standby mode
- The low saturation voltage reduces IC internal heating and allows a high voltage to be applied to the motor. Thus this device can be used even in environments with a high operating ambient temperature.
- There are no constraints on the relationship between the input voltage and the supply voltage. For example, the LB1930MC can be used with VCC = 3V, and VIN = 5V

Benefits

- Low input voltage devices available 2V
- Rugged operation
- Thermal protection
- Low Consumption

Applications

- Industrial
- Consumer
- Portable & Wireless

End Products

- Digital Still Camera
- CD, DVD and Blue Ray Disk player loading motors.
- Thermal printers, portable printers, scanner
- Toy, Battery operate devices

Part Electrical Specifications

Product	Compliance	Status	Type	V _M Min (V)	V _M Max (V)	V _{CC} Min (V)	V _{CC} Max (V)	I _O Max (A)	I _O Peak Max (A)	Step Resolution	Control Type	Feedback Method	Current Sense	Regulator Output	Fault Detection	Flyback Protection	Package Type
LB1930MC-AH	Pb-free Halide free	Active	Brush DC	2.2	11			1			Parallel		None	No	Thermal	Integrated Active	SOIC-10 NB

For more information please contact your local sales support at www.onsemi.com

Created on: 10/11/2013